

PTFE coated fibreglass draw cord-TFDC-1875

Typical Properties	Nominal Values
Thickness	3.5mm
Tensile strength	200 lbs/min
Operating temperature	-72 to +287°C

Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.

**WILLIAM JOHNSTON
& COMPANY LIMITED**

EXCLUSIVE SCOTTISH DISTRIBUTOR

Revision date: 5th February 2021LEADING MANUFACTURER AND SUPPLIER
OF PIPE SAFETY SHIELDS**FLANGE GUARDS.com**

Flangeguards Ltd. Unit 5 Cranes Close, Basildon, Essex SS14 3JB United Kingdom